

FRONT END LOADER


10.2FX

- » Easy to use single lever joystick
- » Quick and easy detachment without any tools
- » Hardened bushes and pin bolted joints
- » Perfect roll back angle
- » Maximum bucket loading capacity of 0.4 m³



FRONT END LOADER 10.2FX WITH BOOSTER BUCKET

NO.	SPECIFICATIONS	UNITS
A	Loader Pin Height	2898 mm
B	Load Over Height	3438 mm
C	Dump Height at 45 degree	3110 mm
D	Reach at Full Height Fully Dumped	952 mm
E	Working Depth	150 mm
F	Reach at Ground	2150 mm
G	Max Dump Angle	45 degree
H	Roll Back at Ground	52 degree
I	Bucket Capacity	0.4 m ³
J	Maximum Payload Capacity of Bucket	600 kg



TRACTOR COMPATIBILITY*:

Mahindra Yuvo Series &
Mahindra OBP, NBP and NST
series (22.37 kW– 37.28 kW)

**Front end loaders are compatible with a
wide range of tractor models.*

TRACTOR COMPATIBILITY

LOADER TYPE

TRACTOR SERIES

APPLICABLE TRACTOR MODEL

10.2FX with
Booster Bucket

Bhoomiputra &
Sarpanch Series

265 OBP, 275 ECO, 415 OBP,
475 OBP, 475 NBP, 475 NST,
575 OBP, 575 NBP, 575 NST,
585 OBP, 585 NST

Yuvo Series

265 YUVO, 275 YUVO, 475 YUVO,
575 YUVO 2WD, 4WD

XP Series

265DI XP Plus, 275DI XP Plus,
275DI XP Plus, 415DI XP Plus,
475DI XP Plus, 575DI XP Plus,
585DI XP Plus



Easy Access to
Service & Spares

Warranty
6 months*



Installation at
Customer Site

Access to
Finance

**or 750 hours
whichever is earlier*

Mahindra & Mahindra Ltd., Farm Equipment Sector Farm Division, AFS Headquarters,
Mahindra Towers, 1st Floor, Akurli Road, Kandivali (E), Mumbai - 400101, India.
Call our Toll-Free Number: 1800-425-6576