

# FRONT END LOADER


## 9.5FX

- » Easy to use single lever joystick
- » Quick and easy detachment without any tools
- » Hardened bushes and pin bolted joints
- » Perfect roll back angle
- » Maximum bucket loading capacity of 0.4 m<sup>3</sup>



## FRONT END LOADER 9.5FX WITH 6 IN 1 BUCKET

NO.	SPECIFICATIONS	UNITS
A	Loader Pin Height	2898 mm
B	Bottom Open Dump Height	3056 mm
C	Dump Full Height	2776 mm
D	Reach at Full Height 45 degree	592 mm
E	Working Depth	150 mm
F	Reach at Ground	1400 mm
G	Roll Back at Ground	60 degree
H	Bucket Opening Distance	708 mm
I	Bucket Capacity	0.38 m <sup>3</sup>
J	Maximum Payload Capacity of Bucket	600 kg



### TRACTOR COMPATIBILITY\*:

Mahindra Yuvo Series &  
Mahindra OBP, NBP and NST  
series (22.37 kW– 37.28 kW)

*\*Front end loaders are compatible with a  
wide range of tractor models.*

Dozing

Grabbing

Grading

Spreading

Loading

Digging

**APPLICATIONS  
OF 6 IN 1  
BUCKET**



## TRACTOR COMPATIBILITY

LOADER TYPE	TRACTOR SERIES	APPLICABLE TRACTOR MODEL
9.5FX with 6 in 1 Bucket	Bhoomiputra & Sarpanch Series	265 OBP, 275 ECO, 415 OBP, 475 OBP, 475 NBP, 475 NST, 575 OBP, 575 NBP, 575 NST, 585 OBP, 585 NST
	Yuvo Series	265 YUVO, 275 YUVO, 475 YUVO, 575 YUVO 2WD, 4WD
	XP Series	265DI XP Plus, 275DI XP Plus, 275DI XP Plus, 415DI XP Plus, 475DI XP Plus, 575DI XP Plus, 585DI XP Plus



Easy Access to  
Service & Spares

Warranty  
6 months\*



Installation at  
Customer Site

Access to  
Finance

*\*or 750 hours  
whichever is earlier*

Mahindra & Mahindra Ltd., Farm Equipment Sector Farm Division, AFS Headquarters,  
Mahindra Towers, 1<sup>st</sup> Floor, Akurli Road, Kandivali (E), Mumbai - 400101, India.  
Call our Toll-Free Number: 1800-425-6576