

Mahindra Gyrovator WLX

*Behtereen Performance,
Mahindra ka Vaada*




Mahindra Gyrovator WLX is a light in weight rotary tiller designed for superior performance in wet land, for both puddling and dry land pulverization.

Key Features ■

Optional Additional Rotor Shaft with L-shaped Blades

Mahindra Gyrovator WLX comes fitted with J-shaped blades. Our customers have the option to buy an additional rotor shaft fitted with L-shaped blades for dry tillage. This way, one can have a versatile rotary tiller and does not have to incur the cost of a whole new rotary tiller.



Mahindra BoroBlades™

High durability blades ensuring lower maintenance costs.

Technical Specifications ■

| Product Specification | WLX 2.05 m | WLX 1.85 m |
|---|---|---|
| Tractor Engine Power Range | 37.3 kW – 44.7 kW (approximately 50 - 60 HP) | 29.8 kW – 37.3 kW (approximately 40 - 50 HP) |
| Overall Width (mm) | 2232 mm | 2032 mm |
| Working Width (mm) | 1934 mm | 1734 mm |
| Weight (kg) (with universal joint) | 415 kg | 390 kg |
| Weight (kg) of only universal joint/propeller shaft | 16.5 | 16.5 |
| Type of Blades * | J L | J L |
| Number of Blades | J type: 44 L type: 48 | J type: 40 L type: 42 |
| PTO r/min | 540 | 540 |
| Rotor Shaft r/min | 204 @ 540 r/min | 204 @ 540 r/min |

*Standard blades are J-type



Easy Access
to Spares



Access to
Finance



Easy Access
to Service



1 year
Warranty*

**Terms and Conditions apply*

Mahindra & Mahindra Ltd., Farm Equipment Sector
Farm Division, AFS Headquarters, Mahindra Towers, 1st Floor,
Akurli Road, Kandivali (E), Mumbai - 400101, India.

Call our Toll-Free Number
1800-425-6576